

Update annotation

This API is responsible for updating an annotation.

[PATCH]/api/v1/annotations/{id}

Response: The id of the updated annotation.

The update operation is only available to the user who created the annotation.

Header

Header used on this API are those taken from [header standards of TS Digital](#).

Content-type is accepted in application/json

Query Parameters

Parameters used to make a successful request.

- **id:** Unique identifier associated with the requested annotation. (**required**)

Body

```
{
  "type": "string",
  "text": "string",
  "classification": "string",
  "ownership": {
    "type": "WS",
    "identifier": "string"
  },
  "referencing_date": "string",
  "reference_period": "string",
  "reference_type": "string",
```

```
"reference_ids": [  
  "string"  
],  
"item_classifier": "string"  
}
```

Each of the fields are optional; only the field included in the request will be updated on the database.

- **type**: specifies the annotation type.
- **text**: contains information about the annotation. Depending on the type, the information contained can be:
 - **note text**: the text value, in case the annotation is of type **NOTE**
 - **folder name**: the name of the folder, in case the annotation is of type **FOLDER**
- **classification**: the classification of the annotation
- **ownership**: specifies the ownership of the annotation. It contains the following 2 fields:
 - **type**: it can be **WS** or **ITEM**
 - **identifier**: the item identifier
- **referencing_date**: the referencing date
- **reference_period**: the year of reference
- **reference_type**: the reference type, at the moment the only possible value is **DOCSTORE**
- **reference_ids**: the ids of the related documents
- **item_classifier**: it can be **ACCOUNTANT** or **COMPANY**

Response

On successful response

If successful, the **API** responds with HTTP code **200(OK)** with the following body:

```
{  
  "id": "string"  
}
```

- **id**: the unique identifier of the annotation

On error response

In the event of an error, the **API** responds with a body **JSON** with the following format:

```
{  
  "code": "string",
```

```
"timestamp": "2022-10-28T13:01:00.754Z",  
"message": "string",  
"subErrors": [  
  {}  
]  
}
```

- **code**: A string representation of the HTTP error code, linked with the returned http error
- **timestamp**: Date and time of the answer, expressed as a string.
- **message**: Message expressing error.

Possible errors are:

- **400**: The request is malformed (parameters with incorrect format, invalid or inconsistent parameters).
- **401**: An authorization token has not been provided or the authorization token provided is invalid (eg: it has expired).
- **403**: The provided token is valid, but the user is not authorized to perform the operation.
- **404**: No annotation found with the given id.
- **500**: An unexpected error occurred.

Revision #2

Created 2022-10-31 14:07:31 UTC by Endri Qejvanaj

Updated 2022-10-31 14:50:34 UTC by Endri Qejvanaj