

Retrieve Intermediaries

This API is responsible for retrieving all intermediaries that are connected to a unique **itemId**.

[GET]/api/v1/{itemId}/intermediary

Response: List of Intermediaries.

Header

Header used on this API are those taken from [header standards of TS Digital](#).

Content-type is accepted in application/json

Query Parameters

Parameters used to make a successful request.

- **itemId**: Unique personal identification of the item associated with the Intermediary requested. Mandatory for personal or technical users. (**required**)

Body

No body is needed to make this request.

Response

On successful response

If successful, the **API** responds with HTTP code **200(OK)** with the following body:

```
{
  "id": "string",
  "taxId": "string",
  "vatNumber": "string",
```

```

    "description": "string",
    "type": "string",
    "itemUuid": "string",
    "deleted": true,
    "deletedAt": "2022-05-05T12:46:42.013Z",
    "deletedBy": "string",
    "createdAt": "2022-05-05T12:46:42.013Z",
    "createdBy": "string",
    "updatedAt": "2022-05-05T12:46:42.013Z",
    "updatedBy": "string"
  }

```

- **id:** Unique identifier.
- **taxId:** Fiscal code associated with the Intermediary requested.
- **vatNumber:** Number of IVA registration associated with the Intermediary requested (11 characters).
- **description:** Description of the Intermediary requested.
- **type:**
- **deleted:** Boolean value , describes if Intermediary requested is deleted or not.
- **deletedAt:** Date of Intermediary if it's deleted.
- **deletedBy:** Item which deleted requested Intermediary.
- **createdAt:** Date of Intermediary creation.
- **createdBy:** Item which created requested Intermediary.
- **updatedAt:** Date of the last update for the requested Intermediary.
- **updatedBy:** Item which updated requested Intermediary.

On error response

In the event of an error, the **API** responds with a body **JSON** with the following format:

```

{
  "code": "string",
  "timestamp": "2022-05-05T12:46:42.016Z",
  "message": "string",
  "subErrors": [
    {}
  ]
}

```

- **code:** A string representation of the HTTP error code, linked with the returned http error
- **timestamp:** Date and time of the answer, expressed as a string.
- **message:** Message expressing error.

Possible errors are:

- **400**: The request is malformed (parameters with incorrect format, invalid or inconsistent parameters).
 - **401**: An authorization token has not been provided or the authorization token provided is invalid (eg: it has expired).
 - **403**: The provided token is valid, but the user is not authorized to perform the operation.
 - **500**: An unexpected error occurred.
-

Revision #13

Created 2022-04-29 12:25:52 UTC by Arbis Malasi

Updated 2022-05-06 08:58:16 UTC by Arbis Malasi